



**A**



## Modular High Bay

- Damp locations(IP54 Ⓐ Ⓑ )/ Wet locations(IP65 Ⓒ ), UGR<19
- Modular design: Free combination
- Easy maintenance: Plug and play Ⓐ ,the driver and light can be replaced freely without tools
- 0-10V/PWM/Resistance dimmable
- Emergency/Dimmable/Sensor function available
- Optional beam angle: 60°/ 90°/ 100°/ 120°
- Lifespan: 50,000hrs
- Warranty: 5 years

• Certificate:   

### 110lm/W(DLC Standard)

Item No.	Module Quantity	Max. Power	CCT	Luminous Flux	CRI	Voltage	PF	Cover	Beam Angle
HB-100W	4	100W	5000K	11000lm	Ra83	AC120-277V 50/60Hz	0.96	Frosted/ Clear/Lens	60°/90°/ 100°/120°
HB-150W	4	150W	5000K	16500lm					
HB-200W	6	200W	5000K	22000lm					
HB-266W	8	266W	5000K	29260lm					
HB-300W	8	300W	5000K	33000lm					

### 140lm/W(DLC Premium)

Item No.	Module Quantity	Max. Power	CCT	Luminous Flux	CRI	Voltage	PF	Cover	Beam Angle
HB-100W	4	100W	5000K	14000lm	Ra83	AC120-277V 50/60Hz	0.96	Frosted/ Clear/Lens	60°/90°/ 100°/120°
HB-150W	4	150W	5000K	21000lm					
HB-200W	6	200W	5000K	28000lm					
HB-266W	8	266W	5000K	37240lm					
HB-300W	8	300W	5000K	42000lm					

CCT Range: 2700K, 3000K, 3500K,4000K, 4500K, 5000K, 5500K,5700K, 6000K, 6500K